



DEPTH	A	B	C	D	E	F
4" & LARGER	-	30"	30"	36"	36"	36"
3" & SMALLER	18"	24"	24"	30"	36"	36"
2-1/2" & SMALLER	12"	24"	24"	24"	30"	30"
WIRING	-	-	BELOW MAIN	-	-	BELOW MAIN

NOTES:

1. LINES MUST HAVE MIN. CLEARANCE OF 4" FROM EACH OTHER & 24" FROM OTHER TRADES
2. RUN WIRING UNDER MAINLINE, TAPE & BUNDLE @ 10' O.C.
3. PROVIDE A 24" LOOP IN ALL WIRING AT CHANGES IN DIRECTION
4. ALL SLEEVES MUST BE 2 TIMES THE DIAMETER OF THE PIPE WITHIN
5. ALL SLEEVES MUST HAVE FOAM AT PIPE OPENING TO PREVENT DIRT ENTRY
6. ALL SLEEVES MUST EXTEND 12" MIN. DISTANCE PAST CURB OR SIDEWALK
7. CONTRACTOR MUST ADJUST MAINLINE AROUND ALL STREET LIGHT LOCATIONS

LD Consulting 2012 (Any deviation or reproduction of this design must be approved in writing by Valley-Wide Recreation & Park District)



VALLEY-WIDE RECREATION & PARK DISTRICT

TRENCHING & SLEEVING

IR-23

REV. 2012